



## Product Data Sheet

### PRODUCT DESCRIPTION

7031-100 Water-Borne Acrylic primer is a single component primer designed to seal and prepare surfaces for NEOFLEX Coatings where a solvent-borne system is not appropriate. 7031-100 is the perfect choice to prime and seal acrylic-based mortar systems generally associated with Exterior Insulated and Finish Systems.

### PRODUCT NUMBER AND COLOR

Standard Color: 7031-100 White

### CURED RESIN PERFORMANCE

Description	Test Method	Results
Water Resistance	ASTM D471	<20%
Adhesion	ASTM D903	5 lb/in
MVT @ 3 Mils	ASTM E96	30 English

### PRODUCT DATA

Description	Test Method	Results
Weight/Gal	ASTM D1475	9.5 lbs/gal
Weight Solids	ASTM D5201	34%
Volume Solids	ASTM D5201	24%
VOC	ASTM D5201	96.66 g/L
Viscosity	ASTM D562	82 KU
Flash Point	ASTM D3278	None
Shelf Life		2 years (unopened container)
Dry Time (8 wet mils)	ASTM D5895	1 hour @ 75°F, 50% RH

### APPLICATION

Surfaces should be clean, dry and structurally sound.

Apply at a rate of 200 - 400 square feet per gallon depending upon surface and condition. May be brushed, rolled or sprayed. DO NOT APPLY WHEN TEMPERATURE IS BELOW 45°F.

### HEALTH AND SAFETY

Read the Material Safety Data Sheet (MSDS) and container labels for detailed health and safety information. This product is intended for industrial use by properly trained professional applicators only.

### STORAGE

Cans of primer material should be stored in a cool (75°F) area.

### AVOID FREEZING

Manufacturer warrants that the standards and qualities of the product described herein will not vary by more than 10% from the tested results set forth above. **MANUFACTURER HEREBY EXPRESSLY DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY AND/OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE.** Buyer must make its own determination of the suitability of any product for its use, whether such product is used alone or in combination with other materials. **To the extent this or any of Manufacturer's products is proven to be defective, Buyer's sole remedy shall be limited to the replacement of such defective product, exclusive of any costs of labor. MANUFACTURER SHALL NOT BE LIABLE OR OBLIGATED FOR ANY LOSS OR CONSEQUENTIAL OR OTHER DAMAGE INCURRED DIRECTLY OR INDIRECTLY BY BUYER OR ANY OTHER PERSON OR ENTITY THAT ARISES IN ANY WAY IN RELATION TO THIS OR ANY OF MANUFACTURER'S OTHER PRODUCTS.** Nothing contained herein shall be construed to constitute inducement or recommendation to practice any invention covered by any patent without authority of the owner of the patent. No Applicator is or should be viewed as an employee or agent of Manufacturer. 02152011/7031-100PD.indd

NEOGARD Div. of JONES-BLAIR

2728 Empire Central - Dallas, Texas 75235 - Phone (214) 353-1600 - Fax (214) 357-7532 - www.neogard.com