

**Product Data Sheet****PRODUCT DESCRIPTION**

7760/7761 primer is a two-component epoxy polyamide primer for use on wood, concrete and metal surfaces prior to application of surface applied waterproofing systems. Mix one part 7760 with one part 7761 by volume.

PRODUCT NUMBERS AND COLORS

Standard colors are:

7760Red
7761Clear

PRODUCT DATA

Description	Test Method	Results
Weight/Gal (mixed)	ASTM D1475	8.5 lbs/gal
Weight Solids (mixed)	ASTM D4209	66%
Volume Solids (mixed)	Calculated	59%
Viscosity (mixed)	ASTM D562	60 KU
VOC (mixed)	EPA Method 24	336 g/L
Flash Point - 7760	ASTM D3278	58°F
Flash Point - 7761	ASTM D3278	45°F
Adhesion (mixed)	ASTM D4541	300 psi

The above tested results are typical values. Individual lots may vary up to 10% from the typical value.

STORAGE

Containers of coating material should be stored in a cool (70°F) area to insure long shelf life. To prevent container rupture due to very high temperature, keep away from heat and/or open flames.

HEALTH AND SAFETY

Read the Material Safety Data Sheet (MSDS) and container labels for detailed health and safety information. This product is intended for industrial use by properly trained professional applicators only.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience; however, it is expressly declared that Seller does not guarantee the result to be obtained in Buyer's process. **SELLER HEREBY EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY FOR FITNESS FOR A PARTICULAR PURPOSE AND/OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED** as to any and all products and/or suggestions described herein, whether such products are used alone or in combination with other materials. Buyer must make its own determination of the suitability of any product for its use, and the completeness of any information contained herein. Nothing contained herein shall be construed to constitute inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. Applicator is an independent contractor of, and should under no circumstances be viewed as an employee or agent of, the NEOGARD® Division of JONES-BLAIR®. 06212010//7760-7761PD.indd

NEOGARD®
Div. of JONES-BLAIR®

2728 Empire Central - Dallas, Texas 75235 - Toll Free (800) 321-6588 - Fax (214) 357-7532 - www.neogard.com