Product Data Sheet

86500 (66XJB) Neogrip Spheres



Description: 86500 Neogrip Spheres (Hempel 66XJB) are glass spheres.

Recommended use: 86500 Neogrip Spheres are used in Neogard flooring systems to provide slip resistance.

Features: Excellent chemical resistance.

Low oil absorption.

Available in North America. Not included in Group Assortment; other regions must confirm.

Colors and packaging:

86500 (66XJB99980) Neutral 50-lb bag

Physical constants:

Size range 150–250 microns

U.S. mesh size 60–100

Specific gravity

Refractive index

1.51

Free iron content, % max

Young's modulus, 106 psi

Rigidity modulus, 106 psi

Hardness (Moh)

Coefficient of friction

2.5

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1.51

1

Dielectric constant
6.9, 106 Hz at 72°F/22°C
Loss tangent
0.0085, 106 Hz at 72°F/22°C
Volume resistivity
6.5 x 1012 ohm-cm at 77°F/25°C

Softening point 1,299°F (704°C) Expansion coefficient 90 in/in/°C x 10-7

Thermal conductivity 0.0036 (cal/sec)(cm2)(°C/cm) at 932°F/500°C

Composition:

SiO₂* 72.5% Na₂O 13.7% CaO 9.8% MgO 3.3% 0.4% Al_2O_3 FeO/Fe₂O₃ 0.2% K_2O 0.1% B_2O_3 0%

Hydrolytic leach resistance:**

Leachate pH 9.4

Leach conductivity 101 mmho/cm

Leach concentrations:25.7 mg/ccTotal alkali18.1 mg/ccCalciumTraceBoron5.4 mg/cc

Silica

*No measurable free crystalline silica content as tested by ASTM C169. **One hour boil under reflux with deionized water. The above tested results are typical values. Individual lots may vary up to 10% from the typical value. Further technical information can be found at www.neogard.com.

Issued: April 2021 Page: 1/2

Product Data Sheet

86500 (66XJB) Neogrip Spheres



Application details:

Application method: According to Neogard Guide Specifications.

Safety: Handle with care. Before and during use, observe all safety labels on packaging, consult Neogard

Safety Data Sheets and follow all local or national safety regulations.

Note: 86500 is for professional use only.

Issued by: Hempel (USA) – 66XJB

This Product Data Sheet ("PDS") relates to the supplied product ("Product") and is subject to update from time-to-time. Accordingly, the buyer/applicator should refer to the PDS current as of the time of delivery. In addition to the PDS, the buyer/applicator may receive some or all of the specifications, statements and/or guidelines listed below or available at www.neogard.com (the "Additional Documents"):

No. Document Description

- 1 PDS
- 2 Guide Specification
- 3 Application Manual
- 4 Other Technical Support Information (i.e. summary application tables, troubleshooting guides, maintenance manuals, chemical resistance charts and other technical information)

In the event of a conflict between this PDS and the Additional Documents, the conflict shall be resolved in accordance with the order of priority set forth above. In addition, the buyer/applicator should refer to the relevant Safety Data Sheet current as of the time of delivery and available at www.neogard.com. Buyer/applicator is responsible for determining the suitability of the intended use of the Product, and Neogard disclaims all responsibility for any use, handling and storage of the Product that is not in accordance with the requirements set forth in the relevant PDS and the Additional Documents. The terms and provisions hereof apply to this PDS, the Additional Documents and any other documents supplied by Neogard in respect of the Product. The Product is supplied and all technical assistance is given subject to the General Conditions of Sale of Hempel Products and/or Services available at www.hempel.com. NEOGARD MAKES NO OTHER WARRANTY THAT EXTENDS BEYOND THE WARRANTY REFERENCED THEREIN INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OR CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. NEOGARD WILL NOT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR BREACH OF ANY EXPRESS OR IMPLIED WARRANTY OR CONDITION, OR THAT IN ANY WAY ARISE IN RELATION TO THE PRODUCT. 86500-PDS ksk 04122021.docx

Neogard®, a part of Hempel

2728 Empire Central - Dallas, Texas 75235 - Phone (214) 353-1600 - Fax (214) 357-7532 - www.neogard.com

Issued: April 2021 Page: 2/2