

Description: FTS 101 (Hempel 884J9)) is a urethane based additive designed for use with FTS 100 methyl-methacrylate (MMA) based primers. FTS 101 is required with all MMA based primers as it dramatically increases bond-ability to all substrates. FTS 101 is an on-site additive, because it reduces the shelf life of MMA based primers significantly. FTS 101 should be added and mixed with MMA based primers immediately before adding FTS BPO(Powder Hardener).

In no case should the use of FTS 101 be considered a substitute for proper preparation of the substrate. Performing bond tests in several areas of every Neogard FTS installation is always necessary.

Recommended use: As an additive to increase bondability to all surfaces using the Neogard FTS Flooring systems.

Features: Seamless repair that is compatible with Moisture Mitigation. Must be mixed with Neogard FTS BPO Initiator.

Availability: Available in North America. Not included in Group Assortment; other regions must confirm.

Colors and packaging:

FTS 101 (884J900000G4,3)	Clear	5-gallon pails
FTS 101 (884J900000G045)	Clear	55-gallon drums

Physical constants:

Shelf Life	1 year	ASTM D562
Cure to Recoat at 75°F/23°C, 50% relative humidity	1 hour	ASTM D3278
Viscosity	65-75 cPs	ASTM D2196
Density	8.34 lbs/gal	ASTM D1475

The above tested results are typical values. Individual lots may vary up to 10% from the typical value. Further technical information can be found at www.neogard.com.

Application details:

Mixing ratio: Refer to FTS BPO Dosing Chart

Pot-life: No significant impact on MMA based primers.

Cure Time: No significant impact on MMA based primers.

Safety: Handle with care. Use with adequate ventilation. No smoking, open flames, or sparks should be permitted in and around the working area. Before and during use, observe all safety labels on packaging and paint containers, consult Neogard Safety Data Sheets and follow all local or national safety regulations.

Surface preparation:	According to Neogard Guide Specifications.
Application conditions:	<p>MMA based primers mixed with FTS 101 should be applied over mechanically prepared concrete substrates at a rate of approximately 100 sq. ft. per gallon. Depending on substrate surface profile and porosity, coverage rate may vary between 80 - 120 sq. ft. / gallon.</p> <p>It is necessary to follow the mix ratios found in the appropriate dosing chart. FTS 101 should be mixed with MMA based primers onsite immediately before adding Neogard BPO (Powder Hardener).</p> <p>Primer mixes are typically applied neat (without fillers or pigments) and should be applied using a roller or brush at a rate that allows for penetration of the concrete substrate but still maintains a continuous coating on the surface.</p> <p>A second coat of primer mixture may be required on a porous substrate or if the coating appears to be inconsistent. Repeat procedures above until a continuous film is formed. Refer to appropriate primer product data sheet for additional information.</p> <p>Whenever possible, the entire contents of a pail or drum of FTS 101 should be used. Excessive headspace containing air in opened containers will reduce product shelf life. Substrate temperature must be between 40°F/4°C and 110°F/32°C.</p>
Preceding coat:	According to Neogard Guide Specifications.
Subsequent coat:	According to Neogard Guide Specifications.
Storage temperature:	Store material in a cool and dry place out of direct sunlight. Do not store near open flame or ignition source.. Recommended temperature: 75°F/23°C.
Remarks:	Must be protected from UV exposure. Should be applied over a mechanically prepared concrete substrate at a rate allowing for penetration of the concrete. The rate of application will depend on the substrate surface profile and porosity.

Note: **FTS 101 is for professional use only.**

Issued by: Hempel (USA) –884J9

This Product Data Sheet (“PDS”) relates to the supplied product (“Product”) and is subject to update from time-to-time. Accordingly, the buyer/applicator should refer to the PDS current as of the time of delivery. In addition to the PDS, the buyer/applicator may receive some or all of the specifications, statements and/or guidelines listed below or available at www.neogard.com (the “Additional Documents”):

No.	Document Description
1	PDS
2	Guide Specification
3	Application Manual
4	Other Technical Support Information (i.e. summary application tables, troubleshooting guides, maintenance manuals, chemical resistance charts and other technical information)

In the event of a conflict between this PDS and the Additional Documents, the conflict shall be resolved in accordance with the order of priority set forth above. In addition, the buyer/applicator should refer to the relevant Safety Data Sheet current as of the time of delivery and available at www.neogard.com. Buyer/applicator is responsible for determining the suitability of the intended use of the Product, and Neogard disclaims all responsibility for any use, handling and storage of the Product that is not in accordance with the requirements set forth in the relevant PDS and the Additional Documents. The terms and provisions hereof apply to this PDS, the Additional Documents and any other documents supplied by Neogard in respect of the Product. The Product is supplied and all technical assistance is given subject to the General Conditions of Sale of Hempel Products and/or Services available at www.hempel.com. NEOGARD MAKES NO OTHER WARRANTY THAT EXTENDS BEYOND THE WARRANTY REFERENCED THEREIN INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OR CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. NEOGARD WILL NOT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR BREACH OF ANY EXPRESS OR IMPLIED WARRANTY OR CONDITION, OR THAT IN ANY WAY ARISE IN RELATION TO THE PRODUCT.

FTS 101-PDS sas 02282023.docx

Neogard®, a part of Hempel
2728 Empire Central - Dallas, Texas 75235 - Phone (214) 353-1600 - Fax (214) 357-7532 - www.neogard.com