

Technical Information

BPO Initiator Dosage Chart for Neogard PMMA/PUMA products

BPO Initiator Dosage by Ambient Air Temperature (fluid ounces per gallon)													
Product	30°F (-1°C)	35°F (2°C)	40°F (4°C)	45°F (7°C)	50°F (10°C)	55°F (13°C)	60°F (16°C)	65°F (18°C)	70°F (21°C)	75°F (24°C)	80°F (27°C)	85°F (29°C)	90°F (32°C)
100 RTS	12	11	10	9	8	7	6	5	4	3.5	3	2.5	2
200 RTS	12	11	10	9	8	7	6	5	4	3.5	3	2.5	2
300 RTS	12	11	10	9	8	7	6	5	4	3.5	3	2.5	2
400 RTS	6	6	5	5	5	4	4	4	3	3	3	2.5	2

Note: 25 fluid ounces of BPO equals 1 pound.

Issued by: Hempel (USA) – Neogard BPO Initiator Dosage Chart

This document is intended for professional use and provides generic advice in respect of the subject matter hereof only. It is not intended to be used as a comprehensive guide. The buyer/applicator should always read the relevant Product Data Sheets ("PDS"), Safety Data Sheets and Guide Specification relating to the applicable products/system. If in doubt, please contact your local Neogard representative for further advice. To the extent relevant, the disclaimer set forth in the relevant PDS or Guide Specification applies to this document. BPOChart-TI ksk 04142021.docx

Neogard®, a Part of Hempel
2728 Empire Central - Dallas, Texas 75235 - Phone (214) 353-1600 - Fax (214) 357-7532 - www.neogard.com