Product Data Sheet 70410-CA (45011) Aromatic Urethane, SCAQMD-Compliant



Description:	70410-CA (Hempel 45011) is a single-component, moisture-cured aromatic urethane.
Recommended use:	As a base coat for Neogard Auto-Gard and Peda-Gard traffic coating systems. Suitable areas include parking garages, stadiums, balconies, plaza decks, walkways, and rooftop recreation areas.
Features:	Meets South Coast Air Quality Management District (SCAQMD) VOC requirements.
Certificates/approvals:	LEED: MRc4, MRc5, IEQc4.2 UL: TGFU.R6034 City of Los Angeles: RR# 25702
Availability:	Available in North America. Not included in Group Assortment; other regions must confirm.

Colors and packaging:

70410-CA (4501116650)	Gray	55- and 5-gallon
Physical constants:		
Tensile Strength Elongation Permanent Set Tear Resistance Water Resistance MVT at 20 mils Taber Abrasion Shore A Adhesion	1,200 psi 400% <10% 100 pli <3% 2.6 English Perm 30 mg/1,000 cs17 70–75 300 psi	ASTM D412 ASTM D412 ASTM D412 ASTM D1004 ASTM D471 ASTM E96 ASTM D4060 ASTM D2240 ASTM D4541
Weight/Gallon Weight Solids Volume Solids VOC Viscosity Flash Point Fire Resistance (Spread of Flame)	11.1 lbs/gal 84% 78% 98 g/L 87 KU 95°F (35°C) Class A (as part of a system) <i>The above tested results are typica</i>	ASTM D1475 ASTM D4209 Calculated EPA Method 24 ASTM D562 ASTM D3278 ASTM E108/UL 790

The above tested results are typical values. Individual lots may vary up to 10% from the typical value. Further technical information can be found at www.neogard.com.

Application details:

Application method: Thinner (max.vol.): Mixing: Cleaning of tools:	Roller or squeegee Acetone (10%) Mix for 3–5 minutes before applying; Jiffy Mixer paddle recommended Acetone
Safety:	Handle with care. Use with adequate ventilation. Before and during use, observe all safety labels on packaging and paint containers, consult Neogard Safety Data Sheets and follow all local or national safety regulations.
Surface preparation:	According to Neogard Guide Specifications.
Application conditions:	Substrate temperature must be between 40°F (4°C) and 110°F (32°C).
Preceding coat:	According to Neogard Guide Specifications.
Subsequent coat:	According to Neogard Guide Specifications.



Accelerators and additives:	7986 (994JB00000): Odor mask, synthetic vanilla scent. 7922 (990JB00000): Enhances sag resistance. 7923 (9505300000): Accelerator for single component urethanes.
Storage temperature:	Store in a cool area to ensure full shelf life. Recommended temperature: 75°F (23°C).
Remarks:	Not intended as a topcoat. Not recommended for constant immersion. Not compatible with asphaltic compounds. For on-grade applications, substrates constructed over unvented metal decks or between-slab applications, contact Neogard Technical Service.

Note:

70410-CA is for professional use only.

Issued by:

Hempel (USA) – 45011

This Product Data Sheet supersedes those previously issued.

Manufacturer warrants that the physical properties of the product reported above will meet the standards and deviations of the associated ASTM test method. MANUFACTURER HEREBY EXPRESSLY DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY AND/OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Buyer must make its own determination of the suitability of any product for its use, whether such product is used alone or in combination with other materials. To the extent this or any of Manufacturer's products is proven to be defective, Buyer's sole remedy shall be limited to the replacement of such defective product, exclusive of any costs of labor. MANUFACTURER SHALL NOT BE LIABLE OR OBLIGATED FOR ANY LOSS OR CONSEQUENTIAL OR OTHER DAMAGE INCURRED DIRECTLY OR INDIRECTLY BUYER OR ANY OTHER PERSON OR ENTITY THAT ARISES IN ANY WAY IN RELATION TO THIS OR ANY OF MANUFACTURER'S OTHER PRODUCTS. Nothing contained herein shall be construed to constitute inducement or recommendation to practice any invention covered by any patent without authority of the owner of the patent. No Applicator is or should be viewed as an employee or agent of Manufacturer. 70410-CA-PDS ksk 03262020.docx

Neogard[®], a part of Hempel 2728 Empire Central - Dallas, Texas 75235 - Phone (214) 353-1600 - Fax (214) 357-7532 - www.neogard.com