

Product Data Sheet

7061 Neocrylic (38AJB) Acrylic Wall Coating, Satin Finish



Description:	7061 Neocrylic (Hempel 38AJB) is an acrylic, water-based, decorative, high-hiding, exterior acrylic coating with a satin finish.
Recommended use:	As a protective and decorative exterior coating over masonry, wood, incidental metal surfaces, and Insulation and Finish Systems (EIFS). Recommended areas include exterior walls, ceilings, columns, and beams.
Features:	Meets OTC and EPA VOC requirements.
Availability:	Special order only. Available in North America. Not included in Group Assortment; other regions must confirm.

Colors and packaging:

7061 (38AJB10000)	White	5-gallon
7061 (38AJB00010)	White Base	

Some colors may have extended lead times and/or minimum quantities. Contact Neogard for colors.

Physical constants:

Tensile Strength	TBD	ASTM D412
Elongation	TBD	ASTM D412
Permanent Set	TBD	ASTM D412
MVT	TBD	ASTM D1653
Reflectivity, Diffuse	TBD	LM 44 1990
Accelerated Weathering	TBD	ASTM G154, 3,000 hours
Gloss at 60°	12.0	ASTM D523
Weight/Gallon	10.74 lbs/gal	ASTM D1475
Weight Solids	49.60%	ASTM D4209
Volume Solids	35.0%	Calculated
Viscosity	100 KU	ASTM D562
VOC	< 150 g/L	EPA Method 24
Flash Point	None	ASTM D3278
Dry Time to Touch*	0.5–1 hour	
Dry Time to Recoat	2–4 hours	
Dry Time to Full Cure	5 days	
Shelf Life	2 years (unopened)	

The above tested results are typical values. Individual lots may vary up to 10% from the typical value. Further technical information can be found at www.neogard.com.

Application details:

Application method:	Roller/Brush/Spray (contact Neogard for spray equipment information)
Thinner (max.vol.):	Do not thin
Mixing:	Mix for a minimum of 3–5 minutes before applying
Cleaning of tools:	Water

Safety: Handle with care. Use with adequate ventilation. Before and during use, observe all safety labels on packaging and paint containers, consult Neogard Safety Data Sheets and follow all local or national safety regulations.

Surface preparation: According to Neogard Guide Specifications.

Application conditions: Apply only when substrate or ambient temperatures are above 40°F/4°C. Do not apply if temperatures are expected to fall below 40°F/4°C within 24 hours after application. Do not apply if rain is expected within 24 hours of application.

Product Data Sheet

7061 Neocrylic (38AJB)

Acrylic Wall Coating, Satin Finish



Note: **7061 is for professional use only.**

Issued by: Hempel (USA) – 38AJB

This Product Data Sheet supersedes those previously issued.

Manufacturer warrants that the physical properties of the product reported above will meet the standards and deviations of the associated ASTM test method. MANUFACTURER HEREBY EXPRESSLY DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY AND/OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Buyer must make its own determination of the suitability of any product for its use, whether such product is used alone or in combination with other materials. To the extent this or any of Manufacturer's products is proven to be defective, Buyer's sole remedy shall be limited to the replacement of such defective product, exclusive of any costs of labor. MANUFACTURER SHALL NOT BE LIABLE OR OBLIGATED FOR ANY LOSS OR CONSEQUENTIAL OR OTHER DAMAGE INCURRED DIRECTLY OR INDIRECTLY BY BUYER OR ANY OTHER PERSON OR ENTITY THAT ARISES IN ANY WAY IN RELATION TO THIS OR ANY OF MANUFACTURER'S OTHER PRODUCTS. Nothing contained herein shall be construed to constitute inducement or recommendation to practice any invention covered by any patent without authority of the owner of the patent. No Applicator is or should be viewed as an employee or agent of Manufacturer. 7061-PDS ksk 05052020.docx

Neogard®, a part of Hempel
2728 Empire Central - Dallas, Texas 75235 - Phone (214) 353-1600 - Fax (214) 357-7532 - www.neogard.com